

## wallen



---

### FRAMING

- Aluminum profile cladd in wood veneer 1-1/2" high x 2-3/8" wide
- Continuous 6" reveal around full perimeter
- Profiles cut in field for precise installation
- Tolerance: +/- 3/4"
- 12 week lead time after approved shop drawings
- Finishes: Natural Oak, Teak, American Walnut, Moka Oak, Black Oak or stain to match samples

---

### GLASS

- Single glazed tempered or laminated: 3/8" to 1/2" thickness
- 1/4" aluminum, polycarbonate mullions or VHB tape: straight, 90 degree, 3-way and variable angle
- Fully sealed with acoustic gaskets
- Glass tailored to space specific design requirements

---

### DOORS

- Doors are flush with the partition on corridor side.
- Swing and sliding doors available in wood framed glass or wood veneer.
- Door jamb module, 6" minimum width
- Acoustic gaskets at door jambs and bottom drop seals for swing doors
- Soft closer at sliding door
- Proprietary aesthetic integrated hardware
- Door allowances: 8'-10" maximum. Transom available for doors higher than 8'-10" ft

---

### SOLID WALLS

- Blind partition seamlessly integrated within the Wallen wall system, 4" wide.
- Full height or with glass transom above
- Magnetic white boards available
- Engineered to support furniture systems, TV monitors, electrical and data wiring

---

### HARDWARE

- Italian designed hardware made by PBA
  - Electric strikes, room schedulers and overhead/floor closers can be accommodated
  - Hardware by other manufacturers can be specified
  - Special finishes available upon request
-