

CERTIFICATE OF COMPLIANCE

Certificate Number 20190822-E479544
Report Reference E479544-20190514
Issue Date 2019-AUGUST-22

Issued to: PROLICHT GMBH
Gewerbepark 9
A-6091 Neu-Goetzens AUSTRIA

**This certificate confirms that
representative samples of**

LIGHT-EMITTING-DIODE SURFACE-MOUNTED
LUMINAIRES

Refer to Addendum Page for Models/Product.

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 1598 and CSA C22.2 No.250.0-18 Standard for
Luminaires,
UL 8750 Standard for Light Emitting Diode Light Sources
for use in Lighting,
CSA C22.2 No. 250.13-17 Standard for Light Emitting
Diode (LED) Equipment for Lighting Applications.


Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190822-E479544
Report Reference E479544-20190514
Issue Date 2019-AUGUST-22

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models/Product

USL, CNL – LED Surface-mounted Luminaire, Ceiling and ceiling pendant.

Model “HYPRO 40” or “IDAHO 40” followed by:

UUUUm length
VV built in situation (AB, HL, SUR, SUS)
WW dimming feature (optional)
XXXXlm luminous intensity (optional)
YYYYYK luminous color (optional)
LED
Insert (optional)
-UL

Model “HYPRO 40” or “IDAHO 40” insert RR SSSSS

RR number of heat sinks per insert (optional)
SSSSS “MAGIQ WWASH” or “MAGIQ WW” or
“MAGIQ 4X” or “MAGIQ 8X” or
“MAGIQ HOLLOW” or “MAGIQ HOLLOW WW”

followed by:

TTTT color of surface (optional)
UUUUm length
LED
XXXXlm luminous intensity (optional)
YYYYYK luminous color (optional)
CRI90 (optional)
WW dimming feature (optional)
-UL



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

